

# Technical information

## Marlin 52



### Characteristics

- With two sealing bars as standard (left/right)
- Optional at no extra cost: One sealing bar (front)
- Double seal as standard (two sealing wires).  
Optional at no extra cost: Cut-off/Wide seal
- Easy-to-remove sealing bars for cleaning and maintenance
- Soft Air as standard to protect the product and vacuum bag
- Digital time control with ten-program memory as standard
- Stainless steel casing and transparent lid
- Supplied with two insert plates for a faster cycle and good product positioning

### Options

- 1-2 Cut-off seal
- Sensor control
- Advanced Control System (ACS)
- Liquid control
- Gas flush

### Accessories

- Thermal label printer (only in combination with ACS)
- Inclined insert plate (for liquids and powders)
- External adapter
- Maintenance set for standard maintenance



Specs	Marlin 52	
Chamber LxWxH (mm)	520x500x200	
Machine LxWxH (mm)	710x700x1025	
Voltage	400V-3-50Hz 230V-3-50Hz 220V-3-60Hz 200V-3-50/60Hz	
Pump capacity 50 Hz/60 Hz (m3)	63 / 76	
Machine cycle 50 Hz/60 Hz (sec.)	11 - 24 / 10 - 21	
Power (kW)	1,5 - 2,4	
Weight (kg)	165	
Net seal length (mm)	2 x 510	
- standard	1 x 590	
- option		
Sealing bar configuration	standard	option
- standard		
- option		

### Dimensions mm

